

STERLING

The "TOUGH GUY"



Heavy Duty Contractor Wheelbarrows

Heavy Duty STERLING Contractor Wheelbarrows outlast, outperform all other brands on the job. Special deep narrow tray design plus Far Forward position on undercarriage means EASIER Lifting and Transport. Carry Heavier Loads with LESS EFFORT. Tire options include: 4 ply pneumatic and No Flats guaranteed with our molded polyurethane POLY-U® tire standard with ball bearing hub. Rollbar Support Unit, (RSU Option) for faster easier load discharge and unit assembly. All trays are finished with a long lasting powder coat finish.



Connections are welded in place for a stronger and longer lasting leg support - **NOT** loosely bolted together



Poly Tray with Dual Wheel Pneumatic Option Shown

SPECIAL OPTIONS

1. Steel Frame and Handles
2. Heavy Duty Roller Bearings
3. Dual Wheels
4. Poly-U® Flat free option
5. Poly Tray 6 or 8 c.u. ft.
6. RSU (Roll Bar Support) Option

CAPACITIES: Model 530 = 5 ½ c.u. ft;
Model 620 = 6 ¼ c.u. ft.

STERLING

The "TOUGH GUY"



Mortar Tubs

STERLING Mortar Tubs transport material from mixer to work area. Used on ground level, decks or scaffold. Deep, narrow design reduces mortar set-up; gives more room on scaffold. Standard models feature Heavy Duty 10 ga. steel tubs with lapped corners and continuous welds. Choice of 6, 10 or 12 cu. ft. capacities; rolling or stationary (fork lift) models; and stationary tubs 16 and 20 cu. ft.

RMT Special Features...

- Heavy Duty guide handle welded to tub sides. Bar stock re-inforcement front and rear.
- 8" front slope for easy mortar removal.
- 8" casters swivel and two rigid casters with mold-on rubber tired wheels. Rating 500 lbs. each.
- Special caster mounting bracket for easy replacement.



SMT Special Features...

- Bar stock re-inforcement front and rear.
- 8" front slope on both ends for easy mortar removal.
- 5" fork clearance.
- Fork lift entry on all sides.



SPECIFICATION CHART

Model	Cu. Ft.	Weight	Length	Width	Height	Side Spread
RMT-6	6	151	34	24	*28	16
RMT-10	10	193	53	24	*28	32
RMT-12	12	215	62	22	*28	38
SMT-6	6	130	39	22	23	18
SMT-10	10	170	57	22	24	36
SMT-12	12	195	65	22	23	44
SMT-16	16	225	65	30	23	20^
SMT-20	20	260	57	44	22	17.5^

* Add 10" length, 5" height for handle

^ per fork



Poly Mixing Tub